

UNITED STATES PATENT AND TRADEMARK OFFICE



UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
09/909,910	07/23/2001	Yoshio Sano	Q65531 9164		
7	7590 03/02/2004	EXAMINER			
	MION, ZINN, MACI	DONG, DALEI			
2100 Pennsylvania Avenue, N.W., Washington, DC 20037			ART UNIT	PAPER NUMBER	
			2875		
			DATE MAILED: 03/02/2004		

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary		Application	on No.	Applicant(s)			
		09/909,91	0	SANO ET AL.			
		Examiner		Art Unit			
		Dalei Don		2875			
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply							
THE - Exte after - If the - If NC - Failu Any	ORTENED STATUTORY PERIOD FOR RE MAILING DATE OF THIS COMMUNICATIO nsions of time may be available under the provisions of 37 CFF SIX (6) MONTHS from the mailing date of this communication. period for reply specified above is less than thirty (30) days, a period for reply is specified above, the maximum statutory per ure to reply within the set or extended period for reply will, by stately received by the Office later than three months after the med patent term adjustment. See 37 CFR 1.704(b).	N. R 1.136(a). In no eve . reply within the staturiod will apply and will apply and will atute, cause the apply	ent, however, may a reply be time story minimum of thirty (30) days Il expire SIX (6) MONTHS from ication to become ABANDONE	nely filed s will be considered timel the mailing date of this co O (35 U.S.C. § 133).	y. ommunication.		
Status							
1)🖂	Responsive to communication(s) filed on 2	0 January 2004	4.				
• —							
3)□	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.						
Disposit	ion of Claims						
5)□ 6)⊠ 7)□	Claim(s) 1-46,48,50-52 and 55-97 is/are pending in the application. 4a) Of the above claim(s) 3,4,6-46,48,50-52 and 55-97 is/are withdrawn from consideration. Claim(s) is/are allowed. Claim(s) 1,2 and 5 is/are rejected. Claim(s) is/are objected to. Claim(s) are subject to restriction and/or election requirement.						
Applicat	ion Papers						
10)⊠	The specification is objected to by the Exame The drawing(s) filed on 23 July 2001 is/are: Applicant may not request that any objection to Replacement drawing sheet(s) including the core The oath or declaration is objected to by the	a)⊠ accepted the drawing(s) b rection is require	e held in abeyance. See ed if the drawing(s) is obj	e 37 CFR 1.85(a). lected to. See 37 Cl			
Priority (under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 09/909,910. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received.							
2) Notice 3) Information	et(s) ce of References Cited (PTO-892) ce of Draftsperson's Patent Drawing Review (PTO-948) mation Disclosure Statement(s) (PTO-1449 or PTO/SB er No(s)/Mail Date		4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other:	ate	O-152)		

DETAILED ACTION

Election/Restrictions

1. Claims 3-4 and 6-46, 48, 50-52 and 55-97 are withdrawn from further consideration pursuant to 37 CFR 1.142(b) as being drawn to a nonelected different embodiment of the present claimed invention, there being no allowable generic or linking claim. Election was made without traverse in Paper filed January 20, 2004.

Claim Rejections - 35 USC § 103

- 2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 3. Claims 1-2 and 5 are rejected under 35 U.S.C. 103(a) as being unpatentable over U.S. Patent No. 6,249,264 to Sano in view of U.S. Patent No. 5,900,694 to Matsuzaki.

Regarding to claims 1-2 and 5, Sano discloses in Figure 4, "the reference numeral 11 indicates a first <u>substrate</u> which is a front <u>substrate</u> formed of, for example, a transparent glass; 17 indicates a transparent dielectric layer; and 18 indicates a protective layer formed of, for example, MgO. These members 11, 17, 18, and the following X, Y <u>electrodes</u> XE, YE constitute what is called a "front panel". Further, the reference numeral 21 indicates a second <u>substrate</u> which is a rear <u>substrate</u>; and 22 indicates an address <u>electrode</u> (A <u>electrode</u>) of a predetermined width formed by printing and firing a

Art Unit: 2875

pattern of a silver paste. These members 21 and 22, and the following members 29, 50, 28 constitute what is called a "rear panel". The PDP 1A is formed by sticking peripheral portions of the front and rear panels together and sealing subsequently" (column 20, lines 32-45).

Sano also discloses in Figure 4, "as a general rule, the dielectric layer 17 together with the protective layer 18 will be called a "dielectric" (which will be used in the following second and third preferred embodiments and their modifications as well)" (column 20, lines 46-50).

Sano further discloses in Figure 4, "reference numeral 28R indicates a phosphor emitting red light R (visible light of a predetermined wavelength) by absorbing an ultraviolet ray of a predetermined wavelength emitted from Xe atom; 28G indicates a phosphor emitting green light G; and 28B indicates a phosphor emitting blue light B. The phosphors 28R, 28G, and 28B are generically called a phosphor 28" (column 20, lines 51-57).

Sano further yet discloses in Figure 4, "reference numeral 29 indicates a barrier rib of a first type formed of a material capable of reflecting visible light and arranged in strips; 30 indicates a discharge space filled with discharge gas including the Xe atoms, such as Penning gas; 41 indicates a strip transparent conductive film (hereinafter referred to as a transparent electrode) consisting of a tin oxide layer or the like; 42 indicates a strip metal film (hereinafter referred to as a metal electrode) consisting of multiple films such as Cr--Cu--Cr or Cr--Al--Cr; and the reference character EG indicates one pixel. The pixel EG consists of three unit luminescent areas EU.sub.R, EU.sub.G, EU.sub.B

Application/Control Number: 09/909,910

Art Unit: 2875

emitting red light R, green light G, and blue light B, respectively (which are generically called a unit luminescent area EU)" (column 20, line 58 to column 21, line 4).

Sano further yet discloses in Figure 4, "reference character S indicates a display surface which is part of the outside surface of the first <u>substrate</u> 11 (second main surface); XE and YE are X and Y <u>electrodes</u>, respectively, arranged at predetermined intervals in parallel with each other on the inside surface of the first <u>substrate</u> 11 (first main surface) and extending along a first direction D1. Each of the X and Y <u>electrodes</u> XE and YE consists of the transparent <u>electrode</u> 41 (main <u>electrode</u>), and the metal <u>electrode</u> 42 (sub<u>electrode</u>) which reduces resistance of the main <u>electrode</u>. The reference numeral 50 indicates a <u>barrier rib</u> of a second type extending along the first direction D1 so as to intersect with the <u>barrier rib</u> of the first type 29. The <u>barrier rib</u> of the second type 50 consists of the same materials as the <u>barrier rib</u> of the first type 29 (for example, a glass paste as a base material). This preferred embodiments is characterized by the <u>barrier rib</u> of the second type 50" (column 21, lines 5-21).

However, Sano does not disclose a single sustain electrode is provided in common for a first and second pixel cell adjacent to each other in the column direction. Matsuzaki teaches in Figure 6a, "three main discharge electrodes 6 and 19 are provided for each two display cell lines, and the central electrode 7 among the three main discharge electrodes 6 and 19 is provided so as to extend over the two display cell lines. According to this arrangement, it is desirable that a bus electrode 192 of the central main discharge electrode 19 among the three main discharge electrodes 6 and 19 has branchlike members 18b on both sides, and the bus electrodes 62 of the other main

Art Unit: 2875

discharge electrodes 6 have branchlike members 18b on one side, and the aforementioned bus electrodes 62 of the other main discharge electrodes 6 are arranged so that the sides thereof on which the branchlike members 18b are provided face the central main discharge electrode 7. The reason is that since the panel is configured like this, the periphery of each display cell can be surrounded by the bus electrodes" (column 8, line 62 to column 9, line 10).

Matsuzaki also teaches in Figure 6a, "according to a further example of the present invention, the main discharge electrodes are provided for each display cell line along the extending direction of the display electrodes, and each main discharge electrode is provided so as to extend over two display cell lines. In this case, it is desirable to provide the branchlike members of each bus electrode on both sides of the bandlike member of the bus electrode" (column 9, line 11-18).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to have construct the sustain electrode of Sano with sustain electrode of Matsuzaki provided in common for a first and second pixel cell adjacent to each other in the column direction in order to provide a high emitting efficiency and being able to emit a bright light and a better contrast while reduce the manufacturing process difficulties; furthermore to perform a discharge emitting display with a relatively small consumption of power.

Art Unit: 2875

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Dalei Dong whose telephone number is (571)272-2370. The examiner can normally be reached on 8 A.M. to 5 P.M..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Sandra O'Shea can be reached on (571)272-2378. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

D.D. February 10, 2004

Sentro O'Shoa pervisory Patent Examinar

CEUTSI SOOD